

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representation of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

## **IMAGES ARE BEST AVAILABLE COPY**

**As rescanning documents *will not* correct images, please do not report the images to the Image Problem Mailbox.**

PATENT  
450100-02802IN THE CLAIMS:

1. (Currently Amended) A signal processing device for multiplexing first and second bit streams, each of said first and second bit streams being formatted in accordance with a different standard, comprising:

a dividing means for dividing said second bit stream into predetermined units;

an adding means for adding a start code in a format corresponding to the standard of said first bit stream to each of said units obtained by dividing said second bit stream; and

a multiplexing means for defining a user operable region in said first bit stream and multiplexing and recording at least part of said second bit stream on said user operable region.

B<sup>1</sup>  
2. (Original) The signal processing device according to claim 1, wherein said start code includes time information and said multiplex means multiplexes and records said first and second bit streams having same time information.

3. (Original) The signal processing device according to claim 2, wherein said time information is the display time when the bit streams are displayed or the decoding time when the bit streams are decoded.

4. (Original) The signal processing device according to claim 1, wherein said dividing means divides said second bit stream into units of frames or those of a plurality of frames.

PATENT  
450100-02802

5. (Currently Amended) A signal processing method for multiplexing first and second bit streams, each of said first and second bit streams being formatted in accordance with a different standard, comprising:

- a dividing step for dividing said second bit stream into predetermined units;
- an adding step for adding a start code in a format corresponding to the standard of said first bit stream to each of said units obtained by dividing said second bit stream; and
- a multiplexing step for defining a user operable region in said first bit stream and multiplexing and recording at least part of said second bit stream on said user operable region.

6. (Original) The signal processing method according to claim 5, wherein said start code includes time information and said multiplex step multiplexes and records said first and second bit streams having same time information.

7. (Original) The signal processing method according to claim 6, wherein said time information is the display time when the bit streams are displayed or the decoding time when the bit streams are decoded.

8. (Original) The signal processing method according to claim 5, wherein said dividing step divides said second bit stream into units of frames or those of a plurality of frames.

9. (Currently Amended) A recording medium storing a program for multiplex first and second bit streams, each of said first and second bit streams being formatted in accordance with a different standard, said program comprising:

PATENT  
450100-02802

a dividing step for dividing said second bit stream into predetermined units;  
an adding step for adding a start code in a format corresponding to the standard of said first bit stream to each of said units obtained by dividing said second bit stream; and  
a multiplexing step for defining a user operable region in said first bit stream and multiplexing and recording at least part of said second bit stream on said user operable region.

10. (Original) The recording medium according to claim 9, wherein said dividing step divides said second bit stream into units of frames or those of a plurality of frames.

B1  
Cont.

11. (Currently Amended) A decoding device adapted to decode decoding a multiplexed bit stream conforming to a first standard format obtained by defining a user operable region in a first bit stream and multiplexing and recording at least part of a second bit stream conforming to a second standard format different from said first standard format, said second bit stream also conforming to a syntax of said first standard format, on said user operable region, said decoding device comprising:

a means for detecting the user operable region in said multiplexed bit stream and extracting the data contained in said user operable region;

a converting means for conducting a predetermined converting operation on said data contained in said user operable region and restoring the second bit stream; and

a decoding means for decoding said first bit stream contained in said multiplex bit stream except said user operable region and said second bit stream.

PATENT  
450100-02802

12. (Currently Amended) A decoding method adapted to decode decoding a multiplexed bit stream conforming to a first standard format obtained by defining a user operable region in a first bit stream and multiplexing and recording at least part of a second bit stream conforming to a second standard format different from said first standard format, said second bit stream also conforming to a syntax of said first standard format, on said user operable region, said decoding method comprising:

a step for detecting the user operable region in said multiplexed bit stream and extracting the data contained in said user operable region;

a step for conducting a predetermined converting operation on said data contained in said user operable region and restoring the second bit stream; and

a step for decoding said first bit stream contained in said multiplex bit stream except said user operable region and said second bit stream.

13. (Currently Amended) A recording medium storing a program for decoding a multiplexed bit stream conforming to a first standard format obtained by defining a user operable region in a first bit stream and multiplexing and recording at least part of a second bit stream conforming to a second standard format different from said first standard format, said second bit stream also conforming to a syntax of said first standard format, on said user operable region, said program comprising:

a step for detecting the user operable region in said multiplexed bit stream and extracting the data contained in said user operable region;

a step for conducting a predetermined converting operation on said data contained in said user operable region and restoring the second bit stream; and

PATENT  
450100-02802

a step for decoding said first bit stream contained in said multiplex bit stream except said user operable region and said second bit stream.

14. (New) The signal processing apparatus of claim 1, wherein said units of said second bit stream conform to a syntax of said standard of said first bit stream.

15. (New) The signal processing apparatus of claim 14, wherein said units of said second bit stream cannot be processed by a processor for processing said first bit stream.

16. (New) The signal processing apparatus of claim 15, wherein said standard of said first bit stream is MPEG 2.

17. (New) The signal processing apparatus of claim 16, wherein said units of said second bit stream are formatted to contain an integer number of bits that is a multiple of eight.

18. (New) The signal processing apparatus of claim 16, wherein said units of said second bit stream are formatted to contain 23 or less consecutive bits having a value of zero.

19. (New) The signal processing method of claim 5, wherein said units of said second bit stream conform to a syntax of said standard of said first bit stream.

20. (New) The signal processing method of claim 19, wherein said units of said second bit stream cannot be processed by a processor for processing said first bit stream.

PATENT  
450100-02802

21. (New) The signal processing method of claim 20, wherein said standard of said first bit stream is MPEG 2.

22. (New) The signal processing method of claim 21, wherein said units of said second bit stream are formatted to contain an integer number of bits that is a multiple of eight.

23. (New) The signal processing method of claim 21, wherein said units of said second bit stream are formatted to contain 23 or less consecutive bits having a value of zero.

24. (New) The recording medium of claim 9, wherein said units of said second bit stream conform to a syntax of said standard of said first bit stream.

25. (New) The recording medium of claim 24, wherein said units of said second bit stream cannot be processed by a processor for processing said first bit stream.

26. (New) The recording medium of claim 25, wherein said standard of said first bit stream is MPEG 2.

27. (New) The recording medium of claim 26, wherein said units of said second bit stream are formatted to contain an integer number of bits that is a multiple of eight.

PATENT  
450100-02802

*B1  
Concl.*

28. (New) The recording medium of claim 26, wherein said units of said second bit stream are formatted to contain 23 or less consecutive bits having a value of zero.

---